M754

WEICHAI | LOVOL

PRODUCT FEATURES

LOVOL M754 is designed for comfort and easy operation. Cabin with A/C allows the operator has an excellent view and comfortable environment, operation handles with ergonomic design make the drive easy and flexible. The strong powertrain enable M754 can meet with utility jobs, transportation, and farming jobs.

- The Doosan 4-cylinders enginemeets StageV emission requirements, with unique speed stability control technology and high-efficiency combustion patent, strong engine power, full combustion, able to effectively reduce oil consumption in operation.
- Newly upgraded LCD dashboard, rear wiper, quick-adjust trailer, quick hitch, reserved front PTO interface.They will greatly improve your comfort and work efficiency

WEICHAI LOVOL INTELLIGENT AGRICULTURAL TECHNOLOGY CO., LTD.

Add: No.192 S Beihai Road,Weifang,Shandong,China. PC: 261206

Tel: +86-536-7527358 Website: www.lovolglobal.com E-mail: lovol_agriexport@global.lovol.com

LOVOL lovol.global LOVOL

PRODUCTS INFORMATION

Stage V Doosan engine

Modern LCD dashboard

Hydraulic output with float function

Radio with Bluetooth

PRODUCT PARAMETER

Model		M754
Power system		
Engine Model		Doosan D24
Emission standard		Stage V
Rated power(kW/HP)		55/75
Rated rotating speed(r/min)		2400
Maximum Torque (N·m)		300
Displacement(L)		2.392/4 cylinds
Air filter		Dry type
Oil tank capacity(L)		60
Transmission system		
Drive type		4WD
Clutch type		11 inch,dry,double action
Gearbox shift mode		synchronizer
Gear quantity		12+12
Creeper gear		N/A
Speed range	Forward(km/h)	2.2-38.2
	Reverse(km/h)	1.9-33.5
Differential lock		Mechannical
Brake type		Wet,disc brake
Parking brake		Independent hand brake
Hydraulic system		
Hydraulic output flow(L/min)		41
Multi-way hydraulic spool valve Quantity		2
Lift control mode		Draft and position control
Maximum lift capacity	at balls(kg)	3000
Working device		
towing device		U-type hook
Traction		Swing drawbar
PTO type		Rear Semi-detached PTO 540/1000
PTO gears		6
Standard tires		
Front tire		300/70R20
Rear tire		380/85R30
Machine body		
Safety Roll Over Protection System		●
Cab	Cab with heater	●
	Cab with AC	●
Overall dimensions		
Length*Width*Height(mm)		CAB:4105X1830X2910 ROPS:4105X1830X2678
Wheel base		2070
Structure weight		2780/2940(cab)

Due to real-time changes involving product batches, product information is subject to such changes and adjustments without notice.